


# Pro Trailer Backup Assist Measurement Card



## Step 4: Record Your Measurements

Use the space below to keep track of your measurements.

<i>Note: Round off measurements to the nearest half inch.</i>		Trailer Name _____	Trailer Name _____
<b>A</b>	The horizontal distance from the license plate to the center of the ball hitch on the trailer.	_____ in (cm)	_____ in (cm)
<b>B</b>	The horizontal distance from the center of the ball hitch to the center of the sticker.	_____ in (cm)	_____ in (cm)
<b>C</b>	The distance from the rear-view camera to the center of the sticker.	_____ in (cm)	_____ in (cm)
<b>D</b>	The horizontal distance from the tailgate to the center of the trailer axle (single axle) <b>OR</b> the center of the trailer axles (two or more axles).	_____ in (cm)	_____ in (cm)


**Return to the vehicle and use the instructions in the Quick Start Guide to enter your measurements into the information display.**

# Pro Trailer Backup Assist Measurement Card

## Step 3: Placing Your Sticker

### Placement Tips

- Perform sticker placement when temperatures are above 32° F (0° C)
- Clean the trailer.
- Place the sticker:
  - On a flat, dry, horizontal surface.
  - Entire sticker must be visible to the camera located in the tailgate handle.
  - Within the green zone as shown below, between 7 inches (17 cm) and 22 inches (55 cm) from the trailer ball hitch.
  - Lengthwise on the trailer tongue.
- Once the sticker is in place, proceed to step 4 (see other side of this card).



**WARNING:** Once placed, sticker cannot be moved. Do not attempt to re-use stickers, if removed.



[ProTrailerBackupAssist.com](http://ProTrailerBackupAssist.com)

Scan the QR code for instructional videos of the Pro Trailer Backup Assist set up.



GL3J19B146 CA